



NOTES

1. ALL CONSTRUCTION SHALL CONFORM TO THE APPLICABLE CITY OF SAVANNAH DEVELOPMENTAL GUIDELINES AND TECHNICAL SPECIFICATIONS INCLUDING, BUT NOT LIMITED TO, SECTION 02200 - EARTHWORK, SECTION 02600 - PAVEMENT AND SECTION 03300 - CAST-IN-PLACE CONCRETE.
2. ALL CORE HOLES SHOULD BE FILLED WITH HOT ASPHALT CONFORMING TO PART 1.03 OF SECTION 02600 OF CITY SPECIFICATIONS OR 4,000PSI FIBER REINFORCED READY MIX CONCRETE PAINTED BLACK BY THE END OF THE NEXT WORK DAY. BEFORE FILLING, ENSURE THE HOLES ARE CLEAN AND DRY AND TACK THEM WITH AC-20 OR AC-30 ASPHALT CEMENT CONFORMING TO PART 1.02 B. PROPERLY COMPACT THE ASPHALT CONCRETE USED FOR FILLING THE HOLE AND LEAVE IT FLUSH WITH THE PAVEMENT.
3. THE CITY RESERVES THE RIGHT TO REQUIRE UNDERDRAIN AND/OR FILTER FABRIC ON THE BASIS OF FIELD TESTING.

**STANDARD CONSTRUCTION
DETAILS**



TYPICAL STREET PAVEMENT SECTION

PLATE NUMBER:

P01

APPROVED:

SIGNATURE ON FILE

CITY ENGINEER

SCALE: N.T.S.

DATED: JANUARY 2009