



NOTES:

1. ASPHALT BLOCK TO BE UNIFORM IN SIZE MEASURING 5"X12"X2.5" AND CONFORM TO ASTM D312 AND HAVE NATURAL FINISH. INSTALL PER MANUFACTURER'S RECOMMENDATIONS.
2. CLAY PAVERS TO BE PINE HALL FLASH RED ENGLISH EDGE HEAVY DUTY OR EQUAL, UNIFORM IN SIZE MEASURING 4"X8"X2.75" WITH BEVELED EDGE AND SPACERS NIBS AND CONFORM TO ASTM C1272-07 TYPE F, APPLICATION PX. INSTALL PER MANUFACTURE'S RECOMMENDATIONS.
3. COMPACT BASE TO 100% STANDARD (ASTM D698) PER SECTION 02200, PART 3.01B OF CITY TECHNICAL SPECIFICATIONS.
4. ALL LATERAL STREET CUTS MUST BE COVERED WITH STEEL PLATES OF SUFFICIENT THICKNESS TO SPAN THE CUT WITHOUT NOTICABLE DEFLECTION. PLATES TO REMAIN IN PLACE UNTIL THE CUT IS REPAIRED.

STANDARD CONSTRUCTION
DETAILS



BRICK PAVEMENT REPLACEMENT

PLATE NUMBER:

P09

APPROVED:

SIGNATURE ON FILE

CITY ENGINEER

SCALE: N.T.S.

DATED: FEBRUARY 2009